

# MPF SERIES / 48mm - 96mm

EN 779 EFFICIENCY: M6-F9  
 MEDIA : Micro Glass Fibre  
 SEPARATORS: Hotmelt  
 FRAME: Galvanized Steel, Aluminum, Stainless Steel, MDF, Plastic  
 PROTECTION GRID: Expanded Galvanized Steel  
 GASKET: Two component, continuous polyurethane  
 FINAL PRESSURE DROP: 450 Pascals  
 OPERATING TEMPERATURE: 80 °C



## MPF FILTERS

Part Number	Filter Class (EN 779)	Width (mm)	Height (mm)	Depth (mm)	Media Area (m <sup>2</sup> )	Air Flow (m <sup>3</sup> /h)	Pressure drop (Pascals)
<b>M6</b> ▶							
MPF-287/592/48-6GN	M6	287	592	48	3,0	1000	65
MPF-492/592/48-6GN	M6	492	592	48	5,0	1600	65
MPF-592/592/48-6GN	M6	592	592	48	6,0	2000	65
MPF-287/592/96-6GN	M6	287	592	96	5,5	1450	80
MPF-492/592/96-6GN	M6	492	592	96	9,0	2400	80
MPF-592/592/96-6GN	M6	592	592	96	11,0	2900	80
<b>F7</b> ▶							
MPF-287/592/48-7GN	F7	287	592	48	3,0	1000	80
MPF-492/592/48-7GN	F7	492	592	48	5,0	1600	80
MPF-592/592/48-7GN	F7	592	592	48	6,0	2000	80
MPF-287/592/96-7GN	F7	287	592	96	5,5	1450	90
MPF-492/592/96-7GN	F7	492	592	96	9,0	2400	90
MPF-592/592/96-7GN	F7	592	592	96	11,0	2900	90
<b>F8</b> ▶							
MPF-287/592/48-8GN	F8	287	592	48	3,0	1000	100
MPF-492/592/48-8GN	F8	492	592	48	5,0	1600	100
MPF-592/592/48-8GN	F8	592	592	48	6,0	2000	100
MPF-287/592/96-8GN	F8	287	592	96	5,5	1450	105
MPF-492/592/96-8GN	F8	492	592	96	9,0	2400	105
MPF-592/592/96-8GN	F8	592	592	96	11,0	2900	105
<b>F9</b> ▶							
MPF-287/592/48-9GN	F9	287	592	48	3,0	1000	145
MPF-492/592/48-9GN	F9	492	592	48	5,0	1600	145
MPF-592/592/48-9GN	F9	592	592	48	6,0	2000	145
MPF-287/592/96-9GN	F9	287	592	96	5,5	1450	150
MPF-492/592/96-9GN	F9	492	592	96	9,0	2400	150
MPF-592/592/96-9GN	F9	592	592	96	11,0	2900	150