

# MPF SERIES / 150mm - 292mm

EN 779 EFFICIENCY: M6-F9  
 MEDIA : Micro Glass Fibre  
 SEPARATORS: Hotmelt  
 FRAME: Galvanized Steel, Aluminum, Stainless Steel, MDF, Plastic  
 PROTECTION GRID: Expanded Galvanized Steel  
 GASKET: Two component, continuous polyurethane  
 FINAL PRESSURE DROP: 450 Pascals  
 OPERATING TEMPERATURE: 80 °C



## MPF FILTERS

Part Number	Filter Class (EN 779)	Width (mm)	Height (mm)	Depth (mm)	Media Area (m <sup>2</sup> )	Air Flow (m <sup>3</sup> /h)	Pressure drop (Pascals)	Energy Rating
<b>M6</b> ▶								
MPF-287/592/150-6GN	M6	287	592	150	7,50	1700	80	E
MPF-492/592/150-6GN	M6	492	592	150	12,50	2800	80	E
MPF-592/592/150-6GN	M6	592	592	150	15,0	3400	80	E
MPF-287/592/292-6GN	M6	287	592	292	7,50	1700	80	E
MPF-492/592/292-6GN	M6	492	592	292	12,50	2800	80	E
MPF-592/592/292-6GN	M6	592	592	292	15,0	3400	80	E
<b>F7</b> ▶								
MPF-287/592/150-7GN	F7	287	592	150	7,50	1700	100	C
MPF-492/592/150-7GN	F7	492	592	150	12,50	2800	100	C
MPF-592/592/150-7GN	F7	592	592	150	15,0	3400	100	C
MPF-287/592/292-7GN	F7	287	592	292	7,50	1700	100	C
MPF-492/592/292-7GN	F7	492	592	292	12,50	2800	100	C
MPF-592/592/292-7GN	F7	592	592	292	15,0	3400	100	C
<b>F8</b> ▶								
MPF-287/592/150-8GN	F8	287	592	150	7,50	1700	120	C
MPF-492/592/150-8GN	F8	492	592	150	12,50	2800	120	C
MPF-592/592/150-8GN	F8	592	592	150	15,0	3400	120	C
MPF-287/592/292-8GN	F8	287	592	292	7,50	1700	120	C
MPF-492/592/292-8GN	F8	492	592	292	12,50	2800	120	C
MPF-592/592/292-8GN	F8	592	592	292	15,0	3400	120	C
<b>F9</b> ▶								
MPF-287/592/150-9GN	F9	287	592	150	7,50	1700	150	B
MPF-492/592/150-9GN	F9	492	592	150	12,50	2800	150	B
MPF-592/592/150-9GN	F9	592	592	150	15,0	3400	150	B
MPF-287/592/292-9GN	F9	287	592	292	7,50	1700	150	B
MPF-492/592/292-9GN	F9	492	592	292	12,50	2800	150	B
MPF-592/592/292-9GN	F9	592	592	292	15,0	3400	150	B