

MW SERIES / 292mm

EN 779 EFFICIENCY: M6-F9
 MEDIA : Micro Glass Fibre
 SEPARATORS: Hotmelt
 FRAME: High Impact Polystyrene
 GASKET: Two component, continuous polyurethane
 FINAL PRESSURE DROP: 450 Pascals
 OPERATING TEMPERATURE: 80 °C



MICROFIL W FILTERS

Part Number	Filter Class (EN 779)	Width (mm)	Height (mm)	Depth (mm)	Media Area (m ²)	Air Flow (m ³ /h)	Pressure drop (Pascals)	Energy Rating
M6 ▶								
MW-M6-01	M6	592	292	292	4,5	1700	80	E
MW-M6-02	M6	592	492	292	7,5	2800	80	E
MW-M6-03	M6	592	592	292	9	3400	80	E
F7 ▶								
MW-F7-01	F7	592	292	292	4,5	1700	115	C
MW-F7-02	F7	592	492	292	7,5	2800	115	C
MW-F7-03	F7	592	592	292	9	3400	115	C
F8 ▶								
MW-F8-01	F8	592	292	292	4,5	1700	120	C
MW-F8-02	F8	592	492	292	7,5	2800	120	C
MW-F8-03	F8	592	592	292	9	3400	120	C
F9 ▶								
MW-F9-01	F9	592	292	292	4,5	1700	145	C
MW-F9-02	F9	592	492	292	7,5	2800	145	C
MW-F9-03	F9	592	592	292	9	3400	145	C