

MVEE ENERGY EFFICIENT V FILTERS / 292mm

EN 779 EFFICIENCY: F7-F9
 MEDIA : Micro Glass Fibre
 SEPARATORS: Hotmelt
 FRAME: High impact polystyrene
 GASKET: Two component, continuous polyurethane
 FINAL PRESSURE DROP: 450 Pascals
 OPERATING TEMPERATURE: 80 °C



ENERGY EFFICIENT V FILTERS

Part Number	Filter Class (EN 779)	Width (mm)	Height (mm)	Depth (mm)	Media Area (m ²)	Air Flow (m ³ /h)	Pressure drop (Pascals)	Energy Rating
F7 ▶								
MVEE-F7-01	F7	292	592	292	10	1700	70	A+
MVEE-F7-02	F7	492	592	292	16	2800	70	A+
MVEE-F7-03	F7	592	592	292	20	3400	70	A+
F8 ▶								
MVEE-F8-01	F8	292	592	292	10	1700	80	A+
MVEE-F8-02	F8	492	592	292	16	2800	80	A+
MVEE-F8-03	F8	592	592	292	20	3400	80	A+
F9 ▶								
MVEE-F9-01	F9	292	592	292	10	1700	95	A+
MVEE-F9-02	F9	492	592	292	16	2800	95	A+
MVEE-F9-03	F9	592	592	292	20	3400	95	A+